

## UltraMatic Liquid Compounds

UltraMatic manufactures compound in a variety of compositions using the highest quality raw materials. We have over 40 years experience to help you choose the product that is best suited for your parts. Our no charge laboratory facility is ready to process your sample parts.

DESCRIPTION	
44Q	44Q is a general purpose cleaner with good rust inhibiting qualities for use on all metals with any media. 44Q can be used in almost any application suspending soils, keeping media clean and free cutting. PH Factor: 8.0 Mix at approximately 2-3 ounces per gallon of water.
MA30	Highly concentrated neutral burnisher for the brightest finish on all metals. Some rust protection. Use with any ceramic or plastic media. PH Factor: Neutral Mix at approximately 1-2 ounces per gallon of water.
24Q	Mildly acidic burnisher with very good cleaning properties. Imparts a brilliant color on any metal except zinc. Has good short term rust inhibiting qualities. PH Factor: 3.6 Mix at approximately 1/2 to 2 ounces per gallon of water.
LR600S	Highly concentrated non-nitrite alkaline rust inhibitor / cleaner / degreaser that provides excellent long term shelf life results on cast iron, powdered metal and other ferrous metals. PH Factor: 8.0 Mix at approximately 2 ounces per gallon of water. For post process dip us 6-8 ounces per gallon of water.
60Q	Alkaline rust inhibitor for use in post process dip tanks , vibratory machine or tumbling barrel. For use on ferrous parts only. Mix at 2-3 ounces per gallon.
LR600	Economical mild alkaline rust inhibitor for ferrous metals only. Excellent rust inhibiting qualities. Light cleaning properties. Excellent for use in dip tanks as post process rust inhibitor. PH Factor: 8.0 Mix at approximately 1-2 ounces per gallon of water.



**UltraMatic Equipment Co.**

Phone: (630)543-4565

Fax: (630) 543-4569

Email: [sales@ultramatic-equipment.com](mailto:sales@ultramatic-equipment.com)

