



ULTRAMATIC EQUIPMENT CO.

Vibratory Finishing Equipment Technology Since 1959

848 S. Westgate Drive · Addison, IL. 60101 · (630) 543-4565
sales@ultrasonic-equipment.com



Made in
the USA


P 8 TUB MACHINE – DIRECT DRIVE SERIES

Ultrasonic **Model P8** Tub Type Vibratory Deburring and Finishing Machine, steel fabricated heavy-duty construction as specified and described below.

Direct Drive Series features a Heavy-Duty Vibratory Motor with easily adjustable weights. This unique design feature eliminates belts and pulleys and supplies 100 % power to the Tub. Requires 50% less HP resulting in huge electrical operation cost savings.

Perfect for all types of jobs from deburring aluminum aircraft parts to cleaning Thread Protectors.

| | |
|----------------------------|--------------|
| Model | P 8 |
| Total Capacity | 8 Cu Ft |
| Tub Width (After Lining) | 18 1/2 " |
| Tub Length (After Lining) | 48 " |
| Machine Length | 58 " |
| Machine Width | 38 " |
| Machine Height | 42 " |
| Shipping Weight | 1100 lbs. |
| Polyurethane Lining | 7/8 " |
| Drive Unit HP / lbs. Force | 1.05 / 2470 |
| Input Voltage: | 230/460/3/60 |



STANDARD FEATURES

- Offset Drive for Superior Finishing Power
- Direct Drive System with Adjustable Weights
- Coil Spring Suspension with Urethane Mounts
- Flo Thru Manifold
- Paint: Twilight Gray Industrial Enamel
- Manual Starter with Overload Protection 230/460-volt 3 phase
- Premium Urethane Cast Lining
- Sound Reduction Tub Cover
- Media Discharge Door with Quick Lock
- Removable Drain with Hose
- Recirculation pump and 7 g tank
- Base with Floor Mounting Pads

For literature, video and additional information please visit www.ultrasonic-equipment.com

STANDARD FEATURES



VIBRATOR MOTOR

- MORE ENERGY TO TUB DUE TO DIRECT DRIVE DESIGN
- EASY ADJUSTABLE WEIGHTS (COVER REMOVED)
- LUBRICATED FOR LIFE
- 50% LESS HP REQUIRED
- RUNS SUPER QUIET



Manual Starter with
Overload Protection



Plug Door with
Quick Lock



Tub Cover Flap



Tank and pump

AVAILABLE OPTIONS

| | |
|---|------------------------------------|
| 110 VOLT VSDT • VARIABLE SPEED DRIVE WITH TIMER, SOLUTION PUMP RECEPTACLE, CORDED PLUG, STAND MOUNTED | |
| ST15FS / ST40FS / ST90FS FILTRATION TANKS | REMOVABLE TUB DIVIDER |
| AUTOMATIC PREMIXING COMPOUND SYSTEM | CASTERS |
| MEDIA AND COMPOUND STARTER KIT | OTHER OPTIONS AVAILABLE ON REQUEST |
| 230/460 VOLT CONTROL PANEL WITH 0 TO 6 HOUR TIMER (DISCONNECT BY CUSTOMER) | |



110v VSDT OPTION includes Variable Speed Drive, Timer, pump receptacle with Corded Plug



ST15FS Option



AUTOMATIC PREMIXING COMPOUND SYSTEM (cover removed)



230/460 V CONTROL PANEL WITH TIMER OPTION