



Ultrasonic Model **P6 VT** Vibratory Deburring and Finishing Machine, steel fabricated heavy-duty construction specified and described below.

**Direct Drive Series** features a Heavy-Duty Vibratory Motor with easily adjustable weights. This unique design feature eliminates belts and pulleys and supplies 100 % power to the Tub. Requires 50% less HP resulting in huge electrical operation cost savings and low decibel levels.

SPECIFICATIONS	
Tub Length Inside after lining	35"
Tub Width Inside after lining	18.5"
Total Capacity	6 Cu Ft
Machine Height	40"
Machine Length	45"
Machine Width	34"
Shipping Weight	950 Lbs.
Lining: 80 Durometer	3/4 "
Input Voltage	110
Drive Unit Centrifugal Force : 1570 lbs.	1800 Rpm
Specifications subject to change	



### STANDARD FEATURES

HIGH SPEED <b>DIRECT DRIVE</b> (OFFSET) FOR SUPERIOR FINISHING POWER	PREMIUM CAST POLYURETHANE LINING
FLEXIBLE TUB COVER FOR SOUND REDUCTION	MEDIA DISCHARGE DOOR
AC VARIABLE SPEED DRIVE W/ DIGITAL DISPLAY	REMOVABLE DRAIN WITH HOSE
110 VOLT TIMER SWITCH & RECEPTACLE W/ CORDED PLUG	ADJUSTABLE AMPLITUDE
COIL SPRING SUSPENSION WITH URETHANE MOUNTS	COMPOUND SPRAY PIPING
LUBRICATED FOR LIFE	RECIRCULATION PUMP AND TANK
HEAVY DUTY METAL TUB AND BASE	ONE YEAR WARRANTY
PAINT: TWILIGHT GRAY INDUSTRIAL ENAMEL	

P6 VT STANDARD FEATURES CONTINUED



High Speed Direct Drive Motor , Adjustable Flywheels and Weights Lubricated for Life



110 VOLT • VARIABLE FREQUENCY SPEED DRIVE / TIMER:  
FOR PUSH BUTTON ADJUSTMENTS TO THE VIBRATION FREQUENCY. INCLUDES 110-VOLT ON OFF TIMER, CORDED PLUG AND PUMP RECEPTACLE, STAND MOUNTED. VFD DIGITAL READOUT IS ADJUSTABLE TO 1800 RPM.



HEAVY DUTY URETHANE LINED TUB INCLUDES PLUG DOOR AND SOLUTION CONNECTIONS AND FLEXIBLE SOUND REDUCTION COVER



SOLUTION TANK AND 110 VOLT PUMP INCLUDED