



ULTRAMATIC EQUIPMENT CO.

Vibratory Finishing Equipment Technology Since 1959



Made in
the USA

SPECIFICATION SHEET

Ultrasonic Model VB7VT Vibratory Deburring and Finishing Bowl Machine. Specified and described below. Wet or Dry applications.

SPECIFICATIONS	
Bowl Diameter	42.5
Channel Width	12.5
Channel Depth	13
Process Capacity	7 Cu. Ft.
Load Capacity	1400 Lbs.
Machine Height	40"
Machine Length	44"
Machine Width	56"
Shipping Weight	1800 Lbs.
Lining: 80 Durometer	3/4 "
Input Voltage	110/1/60
Drive Unit: 2 HP	1725 Rpm
Specifications subject to change	




MODEL VB7-VT INCLUDES
DIRECT DRIVE, 110V TIMER, VFD

STANDARD FEATURES

- CAST PREMIUM POLYURETHANE LINING
- DIRECT DRIVE MOTOR W/ ADJUSTABLE WEIGHTS
- HEAVY DUTY STEEL PLATE FABRICATED BOWL AND BASE
- URETHANE MOUNTED COIL SPRING SUSPENSION
- AC VARIABLE SPEED DRIVE W/ DIGITAL DISPLAY
- 110 VOLT TIMER SWITCH WITH CORDED PLUG STAND MOUNTED
- DISCHARGE DOOR AND REMOVABLE DRAIN
- LUBRICATED FOR LIFE MOTOR
- SOLUTION INPUT VALVE
- RECEPTACLE FOR SOLUTION PUMP
- PAINT: TWILIGHT GRAY INDUSTRIAL ENAMEL
- 1 YEAR WARRANTY

DIRECT DRIVE SERIES ▪ features a Heavy Duty Vibratory Motor with easily adjustable weights. This unique design feature eliminates belts and pulleys and supplies 100 % power to the Tub. Requires 50% less HP resulting in huge electrical operation cost savings.



ADDITIONAL STANDARD FEATURES



High Speed Direct Drive Motor (Lubricated for Life) ,
Adjustable Flywheels and Weights



110 VOLT ▫ VARIABLE FREQUENCY SPEED DRIVE / TIMER:
FOR PUSH BUTTON ADJUSTMENTS TO THE VIBRATION
FREQUENCY. INCLUDES 110-VOLT ON OFF TIMER,
CORDED PLUG AND PUMP RECEPTACLE, STAND
MOUNTED. VFD DIGITAL READOUT IS ADJUSTABLE TO
1800 RPM.

AVAILABLE OPTIONS

ST15FS Filtration System ▫ Includes 15 Gallon Tank with Cover, weirs, Filter Bag & 110-volt Recirculation Pump. Polyethylene Tank ID is 20" L x 15" W x 12" High.

