



Ultramatic Model P3 M Vibratory Deburring and Finishing Machine, steel fabricated heavyduty construction specified and described below.

<u>Direct Drive Series</u> features a Heavy-Duty Vibratory Motor with easily adjustable weights. This unique design feature eliminates belts and pulleys and supplies 100 % power to the Tub. Requires <u>50% less HP</u> resulting in huge electrical operation cost savings and low decibel levels.

SPECIFICATIONS		
Tub Length Inside after lining	28.5"	
Tub Width Inside after lining	15"	
Total Capacity	3 Cu Ft	
Machine Height	40"	
Machine Length	36"	
Machine Width	32"	
Shipping Weight	650 Lbs.	
Lining: 80 Durometer	5/8 "	
Input Voltage	110	
Drive Unit Centrifugal Force : 1570 lbs.	1800 Rpm	
Specifications subject to change		



STANDARD FEATURES

HIGH SPEED DIRECT DRIVE FOR SUPERIOR FINISHING POWER	PREMIUM CAST POLYURETHANE LINING	
FLEXIBLE TUB COVER FOR SOUND REDUCTION	Media Discharge Door	
MANUAL STARTER WITH OVERLOAD PROTECTION 230/460 3 PH	REMOVABLE DRAIN WITH HOSE	
COIL SPRING SUSPENSION WITH URETHANE MOUNTS	ADJUSTABLE AMPLITUDE	
LUBRICATED FOR LIFE	COMPOUND SPRAY PIPING	
HEAVY DUTY METAL TUB AND BASE	RECIRCULATION PUMP AND TANK	
PAINT: TWILIGHT GRAY INDUSTRIAL ENAMEL	ONE YEAR WARRANTY	

P3 M STANDARD FEATURES CONTINUED



High Speed Direct Drive Motor , Adjustable Flywheels and Weights Lubricated for Life



HEAVY DUTY URETHANE LINED TUB INCLUDES PLUG DOOR AND SOLUTION CONNECTIONS AND FLEXIBLE SOUND REDUCTION COVER



MANUAL STARTER (NEMA 4X) 230 OR 460 VOLT 3 PHASE



SOLUTION TANK AND 110 VOLT PUMP INCLUDED